

HIGH - PERFORMANCE BIAS BALL PROBE

LFRE-25

Test Centers
.100" (2.54mm)

Specifications

Mechanical	
Full Travel:	.250" (6.35mm)
Recommended Travel:	.167" (4.24mm)
Mechanical Life Exceeds:	1 x 10 ⁶ Cycles

Operating Temperature	
	-55°C to +105°C
<small>Consult factory for other temperature requirements, and other applications below -40°C</small>	

Electrical (Static Conditions)	
Current Rating:	8 amps
<small>Maximum continuous current, non-inductive at working travel</small>	

Average Probe Resistance	8 mOhms
---------------------------------	---------

Materials and Finishes


Plunger:	High Performance Alloy, LFRE proprietary plating
Barrel:	Work hardened Phosphor Bronze, HPA-GOLD™ plated (I.D. and O.D.) over Hard Nickel
Spring:	Music wire, Nickel Plated
Ball:	Stainless Steel

Spring Force in oz. (grams)

	Order Code	Preload	2/3 travel
Elevated	-6.5	2.65 (75)	6.5 (184)
High	-8	3.49 (99)	8.0 (227)
Ultra High	-10	4.42 (125)	10.0 (283)
Premium	-12	5.08 (144)	12.0 (340)

Receptacle Specifications

SPR-25W-2 ☑ (wire wrap, square post)



- SPR-25W (Crimp termination)
- SPR-25W-1 (Solder cup termination)
- SPR-25W-2 (Wire wrap, square post)
- EPR-25W-2 (Wire wrap, square post)
- SPR-25W-2L (Wire wrap, long square post)
- EPR-25W-2L (Wire wrap, long square post)
- SPR-25W-2LL (Wire wrap, extra-long square post)
- EPR-25W-2LL (Wire wrap, extra-long square post)
- SPR-25W-3 (Connector pin/round post)

Note: EPR receptacles are non-finished versions.

LFRE-1

Test Centers
.075" (1.94mm)

Specifications

Mechanical	
Full Travel:	.250" (6.35mm)
Recommended Travel:	.167" (4.24mm)
Mechanical Life Exceeds:	5 x 10 ⁶ Cycles

Operating Temperature	
	-55°C to +105°C
<small>Consult factory for other temperature requirements, and other applications below -40°C</small>	

Electrical (Static Conditions)	
Current Rating:	6 amps
<small>Maximum continuous current, non-inductive at working travel</small>	

Average Probe Resistance	10 mOhms
---------------------------------	----------

Materials and Finishes

Plunger:	High Performance Alloy, LFRE proprietary plating
Barrel:	Work hardened Phosphor Bronze, HPA-GOLD™ plated (I.D. and O.D.) over Hard Nickel
Spring:	Music wire, Nickel Plated
Ball:	Stainless Steel


Spring Force in oz. (grams)

	Order Code	Preload	2/3 travel
Alternate	-6	2.44 (69)	6.0 (170)
Elevated	-7	2.85 (81)	7.0 (198)
High	-8	3.18 (90)	8.0 (227)
Ultra High*	-10	3.73 (106)	10.0 (283)

* May observe slight decrease in cycle life

Receptacle Specifications

LTR-1W-2 ☑ (wire wrap, square post)



- LTR-1W (Crimp termination)
- LTR-1W-1 (Solder cup termination)
- LTR-1W-2 (Wire wrap, square post)
- LTR-1W-2L (Wire wrap, long square post)
- ELTR-1W-2L (Wire wrap, long square post)
- LTR-1W-2LL (Wire wrap, extra-long square post)
- ELTR-1W-2LL (Wire wrap, extra-long square post)

Note: ELTR receptacles are non-finished versions.

LFRE-72

Test Centers
.050" (1.27mm)

Specifications

Mechanical	
Full Travel:	.250" (6.35mm)
Recommended Travel:	.167" (4.24mm)
Mechanical Life Exceeds:	5 x 10 ⁶ Cycles

Operating Temperature	
	-55°C to +105°C
<small>Consult factory for other temperature requirements, and other applications below -40°C</small>	

Electrical (Static Conditions)	
Current Rating:	3 amps
<small>Maximum continuous current, non-inductive at working travel</small>	

Average Probe Resistance	15 mOhms
---------------------------------	----------

Materials and Finishes

Plunger:	High Performance Alloy, LFRE proprietary plating
Barrel:	Work hardened Beryllium copper, HPA-GOLD™ plated (I.D. and O.D.) over Hard Nickel
Spring:	Music wire, Nickel Plated
Ball:	Stainless Steel

Spring Force in oz. (grams)


	Order Code	Preload	2/3 travel
Alternate	-6	2.63 (75)	6.0 (170)
Elevated	-7	2.05 (58)	7.0 (198)
High	-8	3.18 (90)	8.0 (227)
Ultra High*	-10	3.99 (113)	10.0 (283)

* May observe slight decrease in cycle life

Receptacle Specifications

HPR-72W-4 ☑ (Fastite™ wire termination)

(Shown with DS-62-1 installed)



- HPR-72W (Crimp termination)
- HPR-72W-1 (Solder cup termination)
- HPR-72W-4 (FASTITE® wire termination)
- HPR-72W-28 (Preterminated with 28 AWG wire)
- HPR-72W-30 (Preterminated with 30 AWG wire)

HOW TO ORDER


1. For each probe, specify the probe model, tip style, and spring force as shown in example.

2. Place your order via phone or fax.


Phone 909-625-9390 Fax 909-624-9746

Example: LFRE-25T36-10

probe model	tip style	spring force
-------------	-----------	--------------




LFRE-2518 LFRE-25115 LFRE-25135 LFRE-25140




LFRE-25T LFRE-25T1 LFRE-25T30 LFRE-25T36





LFRE-25A LFRE-25B LFRE-25H LFRE-25I




LFRE-25J LFRE-25L LFRE-25L18 LFRE-25L36




LFRE-25UN LFRE-25V LFRE-25Z LFRE-25Z1




LFRE-118 LFRE-1115 LFRE-1135 LFRE-1140




LFRE-1T LFRE-1T24 LFRE-1T30 LFRE-1UN





LFRE-1A LFRE-1B LFRE-1H LFRE-1I




LFRE-1J LFRE-1L LFRE-1L18 LFRE-1L24




LFRE-1V LFRE-1Z LFRE-1Z1




LFRE-72140 LFRE-72J LFRE-72T1 LFRE-72T20



LFRE-72H LFRE-72I LFRE-7218 LFRE-72115



LFRE-72T38 LFRE-72U




Everett Charles Technologies

A DOVER COMPANY

World Headquarters
 Contact Products Group
 700 East Harrison Avenue
 Pomona, CA 91767
 Tel: 909-625-9390
 Fax: 909-624-9746

©2013 Everett Charles Technologies. All information contained in this document is furnished for the sole purpose of identifying and suggesting the nature of the product and does not warrant the nature or quality of the product. Pogo is a registered trademark. PogoPlus and MicroSharp are trademarks of ECT. Patent #5,801,544. Lit. #1473-02-13

www.ectinfo.com



Lead-Free Pogo[®] Contacts



A variety of LFRE tip styles give you the flexibility to meet your application needs


Probe tips, manufactured with ECT's MicroSharp™ technology, offer the ultimate in long-lasting tip sharpness and contact integrity

A double-roll close offers the industry's best pointing accuracy that helps you hit the smallest test targets with high repeatability

Interaction of the captured ball, bias-cut plunger end and applied spring force guarantees uninterrupted electrical contact with the probe barrel sidewall, virtually eliminating probe related false opens

A shorter plunger permits more spring volume, higher spring force and longer spring life

ECT's precious metal plating process, together with enhanced bias contact, provides highly repeatable conductivity



ECT LFRE: Cleaner Probes, Cleaner Environment.

The Lead Free Challenge

Lead free solder can cause many problems in Circuit Testing. Lead Free Solder has a higher reflow temperature, which can result in harder and stickier solder flux resin and a thicker, harder oxide layer. This thicker layer of resin and oxide is more difficult to penetrate and increases wear on the pogo pin. Lead free solder resin and oxides can also increase debris transfer to spring probes. These are many of the issues found in OSP and No-Clean applications. ECT has developed a new test probe, specifically designed to solve these problems.



ECT New Lead Free POGO® Series

ECT's new Lead Free probe line incorporates a number of features that will significantly reduce the issues that arise when switching to lead free solder as well as those contact issues that arise with OSP and No-Clean solder flux.

- **New Proprietary Plating**

Our new Lead Free probe incorporates a new Harder and Slicker plating that not only resists wear but also reduces solder and debris transfer.

- **PogoPlus Bias Ball Design**

The PogoPlus internal bias ball design guarantees uninterrupted electrical contact with the probe sidewall virtually eliminating probe related false opens.

- **Range of Spring Force Choices:**

Compared to competitors' products, which offer limited spring force options, ECT's LFRE Pogos are available in a variety of spring force choices in 100 mil, 75 mil and 50 mil centers.


- **Pointing Accuracy**

ECT's new Lead Free probe incorporates a double roll close, which offers the industries best pointing accuracy. Increased pointing accuracy is of benefit when using Lead Free solder and/or No-Clean as the probe is less likely to touch the edge of the pad where the solder flux accumulates.


New Proprietary Lead Free Plating vs. the Industry Standard

The industry standard for plated POGO pins is Gold electroplate alloyed either with cobalt or nickel to enhance its hardness. Hardness is increased from 90 Knoop for 99.7% pure electroplated gold to 130 to 200 Knoop when alloyed with nickel or cobalt. ECT's new Proprietary Lead Free plating is significantly harder than the industry's standard gold plating. Our new proprietary plating has a hardness range of 550 to 650 Knoop. This makes the probe tips more durable and less susceptible to solder and material transfer.


Hardness Comparison of Lead Free Proprietary Plating to the Industry Standard



Plating Wear




Industry Standard Gold



New Proprietary Plating

Contaminant Transfer




Industry Standard Gold



New Proprietary Plating

In House Testing


ECT has performed numerous in house tests on our new Lead Free probe in order determine its wear properties and its life against lead free solder and no clean solder flux. The following is a resistance graph of the average resistance of a group of Lead Free probes and Equivalent PogoPlus Steel probes cycled and dragged .010" across pads covered with lead free (SAC) solder with no clean solder flux.



Lead-Free Solder Panel


Lead-Free PogoPlus Benefits vs. Conventional Bias Probes

ECT's new Lead Free probes are designed with the same great performance benefits as our PogoPlus probes.



PogoPlus Bias Design

The enhanced bias-ball design forces contact between plunger and barrel wall at all times, virtually eliminating probe-related false opens.




Conventional Bias Design

Angle of spring coil end matches biased plunger end, compromising bias force and electrical contact.

Tighter Pointing Tolerances

ECT Pogo contacts deliver superior pointing accuracy demonstrated by test results measuring sideload TIR.



Objective


Measure the resistance of ECT's LFRE probes and a standard high performance probe as they are compressed and decompressed. For reliable results, a probe should have a resistance of less than 10 milliohms (with a standard deviation of <5 milliohms) throughout the compression/decompression cycle.

Method

Each probe is placed in a calibrated test station that dynamically measures resistance relative to probe displacement. Displacement resolution is 0.0001 inch. For each increment in displacement, resistance is simultaneously measured with a resolution of 1 milliohm.

Results

Test results of ECT's LFRE probes compared to conventional bias probe performance are shown in the graph below.



Resistance vs. displacement tests show the LFRE probe's more consistent resistivity performance resulting in significantly fewer probe false opens and tighter control of the test process.

Discussion

As the displacement vs. resistance graph clearly shows, the bias ball design of ECT's LFRE outperforms the competitor's probe by demonstrating more repeatable resistivity across its travel range. Because false opens occur when large changes in resistivity occur over short displacements, a steeper slope in the displacement/resistivity curve indicates a greater likelihood of a false reject.

For a more detailed discussion of the test method and results, please ask your ECT salesperson for a copy of the complete test report.