

WT Soldering and Rework

High flexibility for versatile applications




ROMEX

Weller®

An unstoppable lineup...the WT.

The best defense. Weller's new WT Line is an unbeatable contingent of compact, stackable soldering stations that are 90 and 150 Watts and feature 1- or 2-channels.

A 900 W hot air station is also included. They are backwards compatible with a phalanx of irons and accessories, giving you a lineup that can face down most hand soldering challenges.

A cleaner, more organized workbench. The space-saving power units have interlocking, reversible safety rests that offer convenient and safe tip storage.

Table of Contents	3		
WT Stations introduction	2-3	Overview WT Stations and sets	12-13
WT 1 / WT 1H / WT 2M Soldering stations	4-5	Soldering tool sets	14-15
WTP 90 Soldering pencil, WSR safety rest	6	Accessories	16-17
WT 2M Soldering station and microtools	7	Building your Weller workbench	18
WTHA 1 Hot air station	8-9	Technical data	19
WT Tool selection and compatibility matrix	10-11	Locations / Contact information	20



HIGH FLEXIBILITY FOR VERSATILE APPLICATIONS WT LINE

High performance WT soldering stations


- > Up to 150 Watts power
- > User friendly, stackable units
- > Best in class – attractive price/performance ratio
- > Maximum versatility: backwards compatible with existing soldering tools
- > Comprehensive range of accessories
- > Featuring the high performance WTP 90 soldering pencil. Innovative and cost-effective with a tip that performs like a cartridge tip



**~1000
possible iron/tip
combinations
per WT station**


Backwards compatibility

- > All soldering irons of the WSD and WD soldering stations can be connected
- > Microsoldering tools can be connected to the WT 2M



WT 1

- > 1-channel, 90 W station



WT 1H

- > 1-channel, 150 W station
- > Powers irons up to 150 W



WT 2M

- > 2-channel, 150 W station
- > 2 irons can be used simultaneously
- > Can connect with micro-pencil WMRP or WMRP-MS and micro-tweezers WMRT or WMRT-MS with active (cartridge) tips



Space-saving, stackable units

The WT soldering stations can be stacked on the WTHA 1 hot air station, or on each other, saving precious workbench space

The can-do **WT** soldering stations.

These next generation, small but mighty soldering stations aim to please. They are compact enough to fit in your hand and be stacked on top of each other, but versatile and powerful enough to tackle all kinds of soldering jobs from heavy high mass applications to delicate microsoldering (the WT 2M only). The high performance WTs are available in a one-channel 90 W station, and also with 150 W powering one- and two-channel stations. Only the 2-channel WT 2M supports Weller's line of microtools.



Multifunctional LCD screen

- > Detailed overview of all functions
- > Adjustable background illumination
- > Power bar graph shows power output from the station to the soldering iron tip

Front-mounted power switch

Convenient on/off control

Menu buttons provide intuitive navigation

- > Temperature controls
- > Password protection
- > Standby and auto setback modes



2-in-1 WSR Safety Rest

The soldering iron holder can flip between wet and dry cleaning receptacles



ESD safe

Can be trusted for professional use

High performance soldering pencil with easy tip change

Similar to a cartridge system, with the WTP 90 you can easily switch out the heating element while the iron is hot, or simply change only the tip.

WT Line High performance WTP 90 Hybrid soldering pencil

- > High-performance, 90 W Hybrid soldering pencil
- > Combination between Micropencil for highest performance with best heat transfer and passive tip pencils with very good heat transfer while controlling costs.
- > Quick tip change system similar to active cartridge system
- > Automatic standby mode operates from a sensor in the handle which detects when the device is in use

Quick Tip Change

- > Passive tip system allows quick exchange of heating elements when iron is hot
- > Can easily switch out tips with knurled nut
- > Tip replacement independent of the heating element



Powering 2 tools at once, the multifunctional WT 2M.



Compatible with microtools, and more!

Packing 150 W of power, the multifunctional 2-channel WT 2M soldering station is backwards compatible with Weller's microsoldering cartridge tip tools, plus many existing passive tip tools providing high performance, easy handling, and long tip life.

Passive tip tools

- > Supporting a wide range of tools using standard passive tips
- > Best in class portfolio to get the right tool for your application
- > Providing high performance while controlling the costs

Microsoldering pencil

- > Extremely short heat-up time (2 to 6 seconds)
- > Optimum heat transfer
- > Minimized recovery time
- > Quick, easy tip change
- > Providing highest performance

Microsoldering and desoldering tweezers

- > Feature twin parallel adjustable tiplets which allow the soldering and desoldering of very small SMD components
- > When connected to the power unit, the tool is recognized by power unit and assigned the appropriate control parameter. Recalibration is usually unnecessary.

Quick Tip Change

- > Active tip (cartridge) system allows quick, convenient change of entire tip when iron is hot
- > No extra tools required to facilitate the end user's day to day work.
- > 100% toolless – change by hand



A safety rest that flips between sponge AND brass wool.



2-in-1 WSR safety rest

The soldering iron holder is reversible, allowing the user to choose between wet and dry tip cleaning.



Safety rests join together

With the removal of the blue side plates, two or more safety rests can be bolted together.



Weller

weller-tools.com

More than just a lot of hot air, the **WTHA 1** hot air station

The WTHA 1 is a compact 900 W, easy-operating hot air station with a smart temperature profile mode adjustable for diverse rework applications, assuring fast, safe performance.



Product picture similar

ADVANTAGES AT A GLANCE



Multi-function LCD Screen

Unique LC display with a detailed overview of all functions. Adjustable background illumination. Power bar graph allows visual monitoring of the output power from the station to the hot air pencil.




New Menu Button

Provides the ultimate user friendly access to and navigation of the menu structure.



Stackable Units

The WT 1 / WT 1H soldering stations can be stacked on the WTHA 1 hot air station saving space on the workbench.



5 Pre-Sets / Temperature Profile

Up to 5 pre-sets are available to define volume, temperature and time settings. With the profile mode activated, the pre-sets can be run in a selected sequential order.



New Control System

Tandem control with a dual sensor system for twice the performance.



High Power

900 Watts, with up to 100 l / min expanded hot air.



Finger Switch

Activation finger switch located on the ergonomic hand grip.




Flexible Silicone Hose

90 cm long, flexible, heat-resistant silicone hose.

WT TOOL SELECTION AND COMPATIBILITY MATRIX

Active Tip  Power Response  Silver Line 

	90 W	150W	
			
	WT 1 Soldering station, 1 channel	WT 1H Soldering station, 1 channel	WT 2M Soldering station, 2 channels



WMRT/WMRT-MS 2 X 40 W MICROSOLDERING TWEEZERS Slim, cartridge tip tweezers. Ideal for soldering and desoldering of very small SMD components. WMRT Order no.T005 13 174 99N WMRT-MS Order no.T005 29 192 99N				
WMRP/WMRP-MS 55 W MICROSOLDERING PENCILS Fine microsoldering pencil with cartridge tip for microscope work. WMRP Order no.T005 29 171 99N WMRP-MS Order no.T005 13 175 99N				
WTP 90 90 W HYBRID SOLDERING IRON The high-tech iron for universal use with power response tips. Order no.T005 29 222 99N				
WP 65 65 W SOLDERING IRON For delicate and small applications. Order no.T005 29 215 99N				
WP 80 80 W SOLDERING IRON Short tip-to-grip distance for all standard soldering applications. Order no.T005 29 180 99N				
WSP 80 80 W SOLDERING IRON For all standard soldering applications. Order no.T005 29 180 99N				
WP 120 120 W SOLDERING IRON For bigger solder joints. Order no.T005 29 193 99N				
WSP 150 150 W SOLDERING IRON Order no.T005 29 170 99N				
WP 200 200 W SOLDERING IRON For heavy solder applications. Order no.T005 29 199 99N				
WTA 50 2 x 25 W DESOLDERING TWEEZERS 2 x 25 W, for safe desoldering jobs. Order no.T005 13 171 99N				
FE 75 75 W SOLDERING IRON For tip extraction. Order no.T005 29 166 99N				
WHP 80 80 W HEATING PLATE Preheating plate. Order no.T005 27 028 99N				
WSB 80 80 W SOLDER BATH Connectable to all Weller 80 W digital station. Order no.T005 27 040 99N				
WSB 150 150 W SOLDER BATH Connectable to all Weller 150 W stations. Order no.T005 27 704 99N				
ZERO SMOG® TL* Fume extraction unit for volume extraction for up to 2 workplaces. Order no. FT91013699N				
ZERO SMOG® 4V** Fume extraction unit for volume extraction for up to 4 workplaces. Order no.T005 36 606 99N				
ZERO SMOG® 6V** Fume extraction unit for volume extraction for up to 6 workplaces. Order no.T005 36 666 99N				
ZERO SMOG® 20T** Fume extraction unit for tip extraction, connectable for up to 20 workplaces. Order no. T005 36 706 99N				

*With WT HUB
**With WX HUB



WTHA 1
900 W | 1 channel.
Hot air iron integrated



WT 1 Soldering Station

1-Channel Power Unit, 90 W



WT 1H Soldering Station

1-Channel Power Unit, 150 W



WT 2M Soldering Station

2-Channel Power Unit, 150 W



WTHA 1 Hot Air Station

Hot Air Station, 900 W with integrated hot air iron



WT 1010 Set

1-Channel Power Unit, 90 W with WTP 90 hybrid soldering iron (90 W / 24 V), soldering tip XNT A and WSR 200 safety rest



WT 1012 Set

1-Channel Power Unit, 90 W with WSP 80 soldering iron, soldering tip LT B and WSR 201 safety rest



WT 1013 Set

WT 1 power unit with WP 80 soldering iron (80W / 24V), soldering tip LT B and WSR 201 safety rest



WT 1014 Set

1-Channel Power Unit, 90 W with WSP 80ROB soldering iron (80W / 24V), soldering tip LT B and WSR 201 safety rest



WT 1010H Set

1-Channel Power Unit, 150 W with WP 120 soldering iron (120 W / 24 V), soldering tip XT B and WSR 201 safety rest



WT 1011H Set

1-Channel Power Unit, 150 W with WP 200 soldering iron (200 W / 24 V), soldering tip XT B and WSR 202 safety rest



WT 2010M

2-Channel Power Unit, 150 W with WTP 90 hybrid iron and safety rest



WT 2020M

2-Channel Power Unit, 150 W with WMRP micro soldering iron and WMRT micro desoldering tweezers and safety rests





WMRP micro soldering pencil with RT 3 tip and WDH 50 safety rest

Fine slim soldering iron. Ideal for microscope work. High performance by integrated active soldering tip
40 W | 12 V | Tip family RT



WMRT microdesoldering tweezers with RTW 2 tip and safety rest WMRTH

Slim tweezers. Ideal for soldering and desoldering of very small SMD components. Tip family RTW
80 W (2 x 40 W) | 12 V | Tip family RTW



WMRP-MS micro soldering pencil with RT3 MS tip and WDH 50 safety rest

Fine slim soldering iron. Ideal for microscope work. High performance by integrated active soldering tip
40 W | 12 V | Tip family RT-MS according to MIL-STD-2000



WMRT-MS microdesoldering tweezers with RTW2 MS tip and safety rest WMRTH

Slim tweezers. Ideal for soldering and desoldering of very small SMD components.
80 W (2 x 40 W) | 12 V | Tip family RTW-MS according to MIL-STD-2000



WTP 90 hybrid soldering iron set with XNT tip and WSR 200 safety rest

The high-tech iron for universal use with power response tips.
90 W | 24V | Max. temperature 450 °C / 850 °F | Tip family XNT



WP 65 soldering iron set with XNT A tip and WDH 10 safety rest

Small, fast soldering iron. Suitable for fine soldering jobs with a high heat demand.
65 W | 24 V | Max. temperature 450 °C / 850 °F | Tip family XNT



WP 80 soldering iron set with LT B tip and WDH 10 safety rest

Soldering iron for all standard applications with short tip-to-grip design. Comfortable safety rest with 4-step varying inclination.
80 W | 24v | Max. temperature 450 °C / 850 °F | Tip family LT



WSP 80 soldering iron set with LT B tip and KH 18 safety rest

For all standard soldering applications.
80 W | 24 V | Max. temperature 450 °C / 850 °F
Tip family LT



WP 120 soldering iron set with XT B tip and WDH 10 safety rest

Versatile 120 W iron for demanding applications. Can use on small and large components within applications with a higher heat demand.
120 W | 24 V | Max. temperature 450 °C / 850 °F
Tip family XT



WSP 150 soldering iron set with LHT F tip and WDH 30 safety rest

For jobs with extremely high heat requirements and large heat sinks.
150 W | 24 V | Max. temperature 450 °C / 850 °F
Tip family LHT



WP 200 soldering iron set with XHT D tip and WDH 31 safety rest

Heavy power soldering iron. Ideal for those applications with the highest heat demands e.g. LED backpanels or HF shieldings.
200 W | 24 V | Max. temperature 450 °C / 850 °F
Tip family XHT



WTA 50 desoldering tweezers set with WTA 1 tip and AK 51 safety rest

For safe desoldering jobs.
2 x 25 W | 24 V | Max. temperature 450 °C / 850 °F



FE 75 integrated fume extraction iron set with LT B tip and safety rest

Fume extraction soldering pencil. Two-in-one soldering and tip extraction. Includes a 5 mm brush.
75 W | 24 V | Max. temperature 450 °C / 850 °F
Tip family LT





WT compatible fume extraction units



Zero Smog® TL

Portable fume extraction unit, easy to install and operate. Small, economical central system for 2 workplaces.



Zero Smog® 4V

Mobile fume extraction unit for large areas, with built-in turbine and pressure regulator for constant volume flow. Up to 4 work places.



Zero Smog® 6V

Mobile fume extraction for large areas, with a built-in turbine. Up to 6 work places.



Zero Smog® 20T

Mobile tip extraction unit. Up to 20 Weller fume extraction soldering irons can be connected directly to the fume extraction unit.



WFE P

The WFE P is a line voltage tip extraction unit designed to run with one or two FE (Fume Extraction) soldering irons.

& WT peripheral heating plates



WHP 80

Heating plate with heating surface 80 x 50 mm, temperature range 50 °C – 200 °C

& WT compatible soldering bath



Peripheral Solder Bath WSB 80

Solder bath, 80 W, Inside diameter 20 mm, depth 25 mm, temperature range 50 °C – 450 °C, for lead-free solder



WSB 150

Solder Bath, 150 W, 50 °C – 550 °C, for lead-free solder

& WT and WX Hub connectors for Zero Smog® units



WT Hub

To connect the Zero Smog® TL unit



WX Hub

To connect the Zero Smog® 4V, 6V and 20T units



Also offering an extensive selection in professional filtration and Weller® Erem® and Weller® Xcelite® precision tools

Weller®



Autoweg 26
3911 TK Rhenen
The Netherlands
Phone +31-(0)317 398 787
Info@Romex.nl www.Romex.nl

- ✔ ESD Solutions
- ✔ Cleanroom Products
- ✔ Soldering Equipment
- ✔ Test & Measurement

weller-tools.com

Weller® is a registered trademark of Apex Brands, Inc. | © 2017
ATG-2322 | Item no. T551024 | Specifications subject to change without notice.